



GATOR SEAL ROLLS

TDS Revision Date (dd/mm/yyyy): 09/02/2026

Page 1 of 1



TECHNICAL DATA SHEET

Update:

February 9, 2026

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description:

In the application of a sealer to protect and seal a paved surface, will we be using a sprayer, followed by a slit foam roller (**YELLOW for a water-based sealer and a GREY roll design to support the different chemicals found in the solvent-based sealer**) The rolls will be use to seal and to remove the excess sealer or puddle left on the paved surface.



Ideal for:

- Paver and concrete slab
- Remove excess sealant
- Remove any puddle surface sealant

Features:

- Even application
- Absorbs excess sealant
- **YELLOW** roll for water-based sealant
- **GREY** roll for solvent-based sealant
- The roller's slots allow for greater sealant absorption and distribution

STEP-BY-STEP SEALANT APPLICATION

After completing the efflorescence cleaning and all other necessary preparation steps, application can begin. Here are the three main steps required! (Note: After cleaning the efflorescence, you must allow the pavers to dry for 24 to 48 hours before sealing them.)

Step 1 Using an HVLP sprayer, apply a coat of sealer.

Step 2 Best Practice: ([See online video. Two people required.](#))

Apply one coat of sealer using a sprayer in 60 sq ft (5.6 m²) sections. Then, use a foam roller suitable for the sealer type (**YELLOW for water-based or GREY for solvent-based**) to remove excess sealer from the surface and prevent pooling. Ensure there is no pooling or buildup of sealer. If using an Alliance sealer, one coat is sufficient. For perspective, one gallon of sealer should cover approximately 175 square feet (16 square meters) of concrete pavers. However, results may vary depending on the age, density, and water absorption characteristics of the surfaces.



Step 3 Allow the pavers to dry for a full 24 hours.

Packaging:

Product	Color	Dimension	Sealer	Quantity/box
GATOR SEAL ROLL	Yellow	9" US (9"1/2 CAN)	Water base	12 units / box
GATOR SEAL ROLL	Grey	9" US (9"1/2 CAN)	Solvent base	12 units/ box



1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
www.polybind.com - Email : info@polybind.com