



GATOR RESEALER
FOR DRY CAST CONCRETE PAVERS
TDS Revision Date (dd/mm/yyyy): 28/05/2026



TECHNICAL DATA SHEET

- Update:** May 28, 2026
Make sure you have an updated data sheet on hand.
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **GATOR SEAL RESEALER** will penetrate the formula of the existing sealer and reactivate the molecules to create a rejuvenated seal to protect the concrete paver surface; therefore, it helps prevent oil and dirt stains, the damage caused by de-icing salt and the effects of the UV rays.
- Features:**
- Easier to clean and maintain
 - Solvent-based
 - Can be applied over [Gator Wet Look](#) and [Satin Look](#) sealers
 - Rejuvenates surface
 - Helps prevent oil and dirt stains, damage from de-icing salt, and effects from the UV rays
- Coverage:**
- 1 u.s. gal. (3.78 l) covers 175 ft² (16 m²)
 - 5 u.s. gal. (18.9 l) covers 875 ft² (80 m²)
- For use on:** For dry cast concrete pavers
- Please note:**
- Concrete pavers should only be sealed 60 days after their installation date. Consult concrete paver manufacturer's for their recommendation.
 - Concrete pavers & jointing sand **MUST** be 100% dry.
 - Temperature should be between 60°F (16°C) to 85°F (29°C) when sealer is applied.
 - Concrete paver surface temperature should be between 60°F (16°C) to 85°F (29°C) and concrete paver surface must be cool to the touch when sealer is applied.
 - Use [Gator Efflorescence Cleaner](#) to remove ground-in dirt from the surface of concrete pavers. It will make the concrete pavers look clean and vibrant. Applying [Gator Efflorescence Cleaner](#) before a **GATOR SEAL RESEALER** application will assure you of a deeper penetration into the cleaned surface.
 - Apply only one (1) coat.
 - Ensure that the surface has been exposed to dry conditions for 48 hours before applying **GATOR SEAL RESEALER**. Note: If the temperature is above 60°F (16°C), the surface should dry within hours.
 - Wear protective gloves, eye protection and respiratory protection.

Application instructions:



1. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
2. Before starting the project, ensure that there are no rain forecasts for the next 24 hours.
3. First clean concrete pavers with [Gator Clean products](#). Remove all oil, grease and rust stains. Use [Gator Efflorescence Cleaner](#) to thoroughly clean the surface to ensure a proper **GATOR SEAL RESEALER** adhesion.





**GATOR RESEALER
FOR DRY CAST CONCRETE PAVERS**

TDS Revision Date (dd/mm/yyyy): 28/05/2026



4. Wait at least 48 hours at a minimum temperature of 60°F (16°C) with no rain, to make sure that the sand and concrete paver surfaces are dry.
5. Apply one (1) coat of **GATOR SEAL RESEALER** using a foam roller.
6. **GATOR SEAL RESEALER** creates a water-repellent and rain-safe surface after 90 min.
7. Let it dry for 24 hours before using the sealed area.

Coating Category: Low Solids Coatings. VOC Concentration Limits: <120 g/L (grams of VOC per liter of material).

Packaging:	Product	Size	per Box	per Pallet
	GATOR SEAL RESEALER	3.78 L (1 U.S. gal.)	4 units	24 boxes
	GATOR SEAL RESEALER	18.9 L (5 U.S. gal.)		48 pails

LIMITED WARRANTY:

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 32°F (0°C) and away from direct sun to receive the benefit under the Limited Warranty. Gator Seal Resealer is to be used to re-seal over existing solvent based sealers.

This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.

