



**GATOR RESEALER**  
**FOR DRY CAST CONCRETE PAVERS**  
TDS Revision Date (dd/mm/yyyy): 01/04/2022



## TECHNICAL DATA SHEET

- Update:** April 1, 2022  
Make sure you have an updated data sheet on hand.  
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611
- Description:** **GATOR SEAL RESEALER** for concrete pavers is made from acrylic based polymers. Gator Seal Resealer will penetrate the formula of the existing sealer and reactivate the molecules to create a rejuvenated seal to protect the concrete paver surface, therefore helps prevent the oil and dirt penetration, corrosion from de-icing salt and the effects from the UV rays.
- Features:**
- Revives look
  - Can be applied over [Gator Seal Wet Look](#) and [Satin Look](#) sealers
  - Film former
  - Rejuvenates surface
  - Easier to clean and maintain
  - Solvent-based
  - Rain-safe after 90 minutes
  - Works between 60°F (16°C) and 85°F (20°C)
  - Helps resist corrosion from de-icing salt, ultraviolet rays effects, motor oil and grease stains
- Coverage:**
- 1 u.s. gal. (3.78 l) covers 175 ft<sup>2</sup> (16 m<sup>2</sup>)
  - 5 u.s. gal. (18.9 l) covers 875 ft<sup>2</sup> (80 m<sup>2</sup>)
- For use on:** For dry cast concrete pavers
- Please note:**
- Concrete pavers should only be sealed 60 days after their installation date. Consult concrete paver manufacturer's for their recommendation.
  - Concrete pavers & jointing sand **MUST** be 100% dry.
  - Temperature should be between 60°F / 16°C to 85°F / 29°C when sealer is applied.
  - Concrete paver surface temperature should be between 60°F / 16°C to 85°F / 29°C and concrete paver surface must be cool to the touch when sealer is applied.
  - [Gator Efflorescence Cleaner](#) to remove ground in dirt from the surface of concrete pavers. It will make the concrete pavers look clean and vibrant. Applying [Gator Efflorescence Cleaner](#) before a **GATOR SEAL RESEALER** application will assure you of a deeper penetration into the cleaned surface.
  - Just use 1 layer of **GATOR SEAL RESEALER**.
  - When using **GATOR SEAL RESEALER** assure yourself at least 48 hours of dry conditions prior to applying **GATOR SEAL RESEALER**. If temperature is above 60°F / 15°C the surface should dry within hours.
  - Wear protective gloves, eye protection and respiratory protection.
  - This sealer is to be employed without thinning or diluting under normal environmental conditions. Use acetone for cleaning. Alliance Designer Products shall not be liable for any non-compliant use.
  - Questions? Visit the [Gator Sealer FAQ page](#).





**GATOR RESEALER  
FOR DRY CAST CONCRETE PAVERS**  
TDS Revision Date (dd/mm/yyyy): 01/04/2022

**Application instructions:**



1. A. ALWAYS REFER to the latest **GATOR SEAL RESEALER** [Technical Data Sheet \(TDS\)](#) at [Polybind.com](#) before installing **GATOR SEAL RESEALER**.  
 B. ALWAYS TEST the product on a small hidden area of approximately 4 sq. ft. (0.4 sq. m.) to ensure the results will meet your expectations.
2. Remove all the stains from the concrete pavers, using [Gator Clean](#) products. Use [Gator Clean Sealer Stripper](#) to remove any unknown coating that remains on the concrete paver surface. (Photo 1)
3. Remove all contaminated jointing material and replace with [Polybind Polymeric Sand](#). Follow the instructions on the back of the bags for proper sand installation. (Photo 2)
4. Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain for the [Polybind Polymeric Sand](#) to properly harden.
5. Clean the entire surface with the [Gator Efflorescence Cleaner](#). This product will remove the efflorescence trapped in the concrete paver pores as well as thoroughly clean the surface for proper sealer adhesion (Photo 3)
6. Wait at least 48 hours at a minimum temperature of 60°F (16°C) and no rain so the sand & concrete paver surface are dry.
7. Best Practice: ([See online video. 2 people needed.](#)) Apply one (1) coat of **GATOR SEAL RESEALER** using a sprayer in 60 sq. ft. sections, then use a solvent-resistant foam roller (black) to remove the excess sealer left on the surface. (Photo 4)
8. **GATOR SEAL RESEALER** is water repellant, rain safe, after 90 minutes.
9. Let the sealer dry for 24 hours before using the sealed area.

**Coating Category:** Low Solids Coatings. VOC Concentration Limits: <120 g/L (grams of VOC per liter of material).

<b>Packaging:</b>	<b>Product</b>	<b>Size</b>	<b>per Box</b>	<b>per Pallet</b>
	<b>GATOR SEAL RESEALER</b>	3.78 L (1 U.S. gal.)	4 units	24 boxes
	<b>GATOR SEAL RESEALER</b>	18.9 L (5 U.S. gal.)		48 pails

**LIMITED WARRANTY:**

Before applying the product, the user/buyer must determine its suitability for intended use and user/buyer assumes all risks in that regard. It is a condition of the Limited Warranty that before using the product on the intended larger area, the user/buyer must first test the product on a small less observed area of approximately 4 sq. ft. (0.4 sq. m.) to ensure results meet user/buyer's expectations. In the event that no test is carried out, the Limited Warranty will only apply to 4 sq. ft. (0.4 sq. m.). ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation ALLIANCE DESIGNER PRODUCTS INC. is to refund the purchase price. Proof of purchase is required for any claim. ALLIANCE DESIGNER PRODUCTS INC. shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, ALLIANCE DESIGNER PRODUCTS INC. excludes any implied warranty of quality, merchantability or fitness for purpose. The container must at all times be stored at above 32°F (0°C) and away from direct sun to receive the benefit under the Limited Warranty.

